




WÖHWA VEES Ö 2L

Vollelektronischer Endschalter/electronic limit switch/fin de course électronique



Artikelnummer order number numéro d'article	NBN8-18GM60-WO	
Ersetzt Artikelnummer replaces article remplace l'article	- 6503421704	
Betriebsspannung supply voltage voltage d'alimentation	U _s	20 ... 253 V AC
Nennschaltabstand rated operating distance portée nominale	S _n	8 mm
gesicherter Schaltabstand safe operating distance portée secure	S _a	0 ... 6,48 mm
Betriebsstrom operating current courant de régime	I _B	<= 200 mA
Reststrom residual current courant résiduel	I _r	<= 1,7 mA
Kurzzeitstrom momentary current courant instantané	I _k	< 1,6 A
Spannungsabfall voltage drop chute de tension	D _d	<= 8 V
Frequenz des Versorgungsnetzes mains supply frequency fréquence du réseau d'alimentation	f	45 ... 65 Hz
Schaltfrequenz operating frequency fréquence des opérations	f _s	0 ... 20 Hz
Bereitschaftsverzug stand-by delay retard d'alerte	t _v	< 100 ms
Schutzart degree of protection genre de protection	IP67, schutzisoliert IP67, protective insulation IP67, double isolation	
Schaltfunktion switching function fonction de contact	AC, Öffner AC, NC AC, NF	
Anzeige display affichage	LED	
Bauform / Einbau in Metall installation type / in metal type d'installation / en méta	M18x1, nicht bündig M18x1, non flush mounted M18x1, pas rogner à fleur	
Anschluss Ausführung connection cable câble de raccordement	PVC-Kabel, 2 m / 2 x 0,34 mm ² PVC-cable, 2 m / 2 x 0,34 mm ² câble C.P.V., 2 m / 2 x 0,34 mm ²	
Anschlussschema / Adernfarben connection diagram / wire colours schéma des connexions / couleurs des connecteurs	BN - braun BU - blau	GN/YE - grün/gelb
	BN - brown BU - blue	GN/YE -green/yellow
	BN - brun BU - bleu	GN/YE - vert/jaune
Umgebungstemperatur operating temperature temperature ambiante	T	-25°C ... +70°C

